



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 588 WATERBORNE BASECOAT BLEND
SECTION 01: Chemical product and company identification

Product name..... PF 588 WATERBORNE BASECOAT BLEND
 Manufactured for..... Pro Form Products Ltd.
 604 McGeachie Drive
 Milton, Ontario L9T3Y5
 Tel (905) 878-4990 Fax (905) 878-1189
 24 hour emergency number:..... IN CANADA CALL CANUTEC 1-888-226-8832 (CAN-UTEC) - IN THE UNITED STATES
 CALL CHEMTREC 1-800-424-9300.
 Recommended use and restrictions on use.. Paint reducer.
 Chemical family..... Mixture.
 Hazard rating
 NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.
 HMIS..... H: 2 F: 4 R: 0.

SECTION 02: Hazards identification


Signal Word..... DANGER.
 Hazard Classification..... Aerosol 1. Flammable Aerosol 1. Single Target Organ Toxicity - Single Exposure 3. Eye Irritant 2.
 Hazard Description..... H222 Extremely flammable aerosol . H229 Pressurized container: may burst if heated.
 H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
 Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P251 Do not pierce or burn container, even after use. P261 Avoid breathing mists, vapours and sprays. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50C / 122F.

SECTION 03: Composition/Information on Ingredients

| HAZARDOUS INGREDIENTS | CAS # | WT. % |
|-----------------------|----------|-------|
| DIMETHYL ETHER | 115-10-6 | 40-70 |
| Acetone | 67-64-1 | 10-30 |
| Isopropyl Alcohol | 67-63-0 | 5-10 |

SECTION 04: First aid measures

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
 Skin contact..... Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
 Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
 Ingestion..... Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
 Additional information..... Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

PRODUCT: PF 588 WATERBORNE BASECOAT BLEND**SECTION 05: Fire fighting measures**

Suitable and unsuitable extinguishing media Carbon dioxide. Water fog. Dry chemical. In cases of larger fires, water spray should be used.

Hazardous combustion products..... Oxides of carbon (CO, CO₂).

Special fire fighting procedures..... Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control.

SECTION 06: Accidental release measures

Leak/spill..... Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).

SECTION 07: Handling and storage

Handling procedures..... Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.

Storage needs..... Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight. Do not store above 49C.

SECTION 08: Exposure controls / personal protection

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL | NIOSH |
|---------------------------------------|-----------------|-------------------|-----------------|------------------|-----------------|-----------------|
| DIMETHYL ETHER | Not established | Not established | Not established | Not established | Not established | Not established |
| Acetone | 500 ppm | 750 ppm | 1,000 ppm | Not established | 250 ppm | |
| Isopropyl Alcohol | 200 ppm | 400 ppm | 400 ppm | 500 ppm | 400 ppm | |
| Protective equipment | | | | | | |
| Eye/type..... | | | | | | |
| Respiratory/type..... | | | | | | |
| Gloves/ type..... | | | | | | |
| Clothing/type..... | | | | | | |
| Footwear/type..... | | | | | | |
| Other/type..... | | | | | | |
| Appropriate engineering controls..... | | | | | | |
| Exposure limits | | | | | | |

Liquid chemical goggles.
Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.
Chemical resistant gloves.
Wear adequate protective clothes.
Safety boots per local regulations.
Emergency showers and eye wash stations should be available.
Local exhaust at points of emission.

SECTION 09: Physical and chemical properties

Physical state..... Aerosol.

Colour..... Clear, colourless.

Odour..... Solvent odour. Amine.

Odour threshold (ppm)..... Not available.

Vapour pressure (mm Hg)..... 80 psig @ 70f.

Vapour density (air=1)..... >1.

pH..... Not applicable.

Relative Density (Specific Gravity)..... 0.72.

Melting / Freezing point (deg C)..... > -95°C .

Solubility..... Miscible.

Initial boiling point / boiling range (deg C)..... -25 t0 +60c.

Evaporation rate..... Similar to water.

Flash point (deg C), method..... -41 Tag Closed Cup (propellant) / -20 for product.

Auto ignition temperature (deg C)..... 350°C.

Upper flammable limit (% vol)..... 27.

PRODUCT: PF 588 WATERBORNE BASECOAT BLEND**SECTION 09: Physical and chemical properties**

Lower flammable limit (% vol)..... 3.4.
 Coefficient of water/oil distribution..... Not available.
 % Volatile by volume..... 100.

SECTION 10: Stability and reactivity

Chemical stability..... Stable at normal temperatures and pressures.
 Reactivity Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. Risk of bursting of closed containers due to an increase in pressure.
 Conditions to avoid..... Keep away from heat. Incompatible with strong oxidizers.
 Hazardous decomposition products..... By fire: Dense black smoke. Oxides of carbon (CO,CO2).
 Possibility of hazardous reactions..... Hazardous polymerization will not occur.

SECTION 11: Toxicological information

| INGREDIENTS | LC50 | LD50 |
|----------------------------------|--|--|
| DIMETHYL ETHER | 308.5 mg/L 4 hours rat | No data |
| Acetone | 50,100 mg/m3 8 hours rat inhalation | 5,800 mg/kg rat oral |
| Isopropyl Alcohol | 16,000 ppm 8 hours rat | 5,000 mg/kg rat oral 12,800 mg/kg rabbit dermal |
| Route of entry | Eye contact. Skin contact. Inhalation. | |
| Effects of chronic exposure..... | Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal . | |
| Skin contact..... | Can cause moderate irritation, defatting and dermatitis. | |
| Skin absorption..... | May be harmful if absorbed through the skin. | |
| Eye contact..... | Can cause redness, irritation, tissue destruction. | |
| Inhalation (acute)..... | Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness. | |
| Inhalation (chronic)..... | Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties. | |
| Ingestion..... | May be harmful or fatal if swallowed. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. | |
| Carcinogenicity of material..... | None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen. | |
| Reproductive effects..... | No data. | |
| Toxicological Data | | |

SECTION 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
 Persistence and degradability..... Not available.

SECTION 13: Disposal considerations

Waste disposal..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.

SECTION 14: Transport information

TDG Classification..... UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre.
 IATA Classification (Air)..... UN1950 -Aerosols - Class 2.1.
 IMDG Classification (Marine)..... UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity.
 Marine Pollutant..... No.

PRODUCT: PF 588 WATERBORNE BASECOAT BLEND

SECTION 15: Regulatory information

WHMIS 1988 classification..... A. B5. D2B.
 CEPA status..... On Domestic Substances List (DSL).
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous substances None.
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... Isopropyl alcohol.
 EPA hazardous air pollutants (HAPS) None.
 40CFR63
 TSCA inventory status..... All components are listed.
 California Proposition 65..... This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.

SECTION 16: Other information

Prepared by: REGULATORY AFFAIRS.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Preparation date: AUG 25/2016