		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 05/19/2017
		Print Date: 12/2/2019
		SDS Number: R0172415
Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD MOTOR OIL		Version: 1.0
3088		

GHS classification in accordance with the Hazardous Products Regulations

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier**

Trade name : Valvoline™ MP 2 CYCLE TC-W3  
OUTBOARD MOTOR OIL

<p><b>Details of the supplier of the safety data sheet</b> Valvoline Canada Corp 905 Winston Churchill Blvd Mississauga ON L5J 4P2 Canada 1-800-TEAMVAL</p>	<p><b>Emergency telephone number</b> 1-800-VALVOLINE (1-800-825-8654)</p> <p><b>Regulatory Information Number</b> 1-800-TEAMVAL</p> <p><b>Product Information</b> 1-800-TEAMVAL</p>
---	---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

Flammable liquids : Category 4

Skin irritation : Category 2

**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H227 Combustible liquid.  
H315 Causes skin irritation.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of water.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 12/2/2019

SDS Number: R0172415

Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD  
MOTOR OIL

Version: 1.0

3088

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 Store in a well-ventilated place.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Static Accumulator

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	Not a hazardous substance or mixture.	>=30.00 - < 50.00
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	Flam. Liq. 4; H227 Skin Irrit. 2; H315 PHNOC 1;	>=20.00 - < 30.00
Naphtha (petroleum), heavy aromatic	64742-94-5	Asp. Tox. 1; H304 PHNOC 1;	>=1.00 - < 5.00

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 12/2/2019

SDS Number: R0172415

Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD  
MOTOR OIL


Version: 1.0

3088

- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.  
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.  
No symptoms known or expected.  
Causes skin irritation.
- Notes to physician : No hazards which require special first aid measures.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air

		Page: 4
<b>SAFETY DATA SHEET</b>		Revision Date: 05/19/2017
		Print Date: 12/2/2019
		SDS Number: R0172415
Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD MOTOR OIL		Version: 1.0
3088		

and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.

Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide  
nitrogen oxides (NO<sub>x</sub>)  
Hydrocarbons

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.  
Suppress (knock down) gases/vapours/mists with a water spray jet.

---

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Container hazardous when empty.



<b>SAFETY DATA SHEET</b>	Revision Date: 05/19/2017
	Print Date: 12/2/2019
	SDS Number: R0172415
Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD MOTOR OIL  3088	Version: 1.0


Avoid contact with skin and eyes.  
 Smoking, eating and drinking should be prohibited in the application area.  
 For personal protection see section 8.  
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
 Observe label precautions.  
 No smoking.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	0.2 mg/m3 Mist	CA BC OEL
		TWA	1 mg/m3 Mist	CA BC OEL
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA	200 mg/m3 (total hydrocarbon vapor)	CA BC OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
		TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	525 mg/m3	CA ON OEL

		Page: 6
<b>SAFETY DATA SHEET</b>		Revision Date: 05/19/2017
		Print Date: 12/2/2019
		SDS Number: R0172415
Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD MOTOR OIL		Version: 1.0
3088		

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:  
Impervious clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Discard gloves that show tears, pinholes, or signs of wear.  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : liquid

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : <-38 °F / -39 °C

Boiling point/boiling range : > 356 °F / 180 °C  
(1013 hPa)

Flash point : 196 °F / 91 °C

Evaporation rate : 0.1  
butyl acetate=1

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 12/2/2019

SDS Number: R0172415

Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD  
MOTOR OIL

Version: 1.0

3088

Flammability (solid, gas)	: No data available
Upper explosion limit	: 6.0 %(V)
Lower explosion limit	: 1.0 %(V)
Vapour pressure	: 0.2 mmHg (20 °C)
Relative vapour density	: No data available
Relative density	: No data available
Density	: Average 0.8550 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 36.8 mm <sup>2</sup> /s (40 °C)
Oxidizing properties	: No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. None known.

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 12/2/2019

SDS Number: R0172415

Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD  
MOTOR OIL

Version: 1.0

3088

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

**SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion**Acute toxicity**

Not classified based on available information.

**Components:**

Distillates, petroleum, solvent-refined heavy paraffinic:

Acute oral toxicity : LD50 (Rat): &gt; 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Not classified as acutely toxic by inhalation under GHS.  
Remarks: No mortality observed at this dose.Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Acute oral toxicity : LD50 (Rat): &gt; 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.28 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Naphtha (petroleum), heavy aromatic:

Acute oral toxicity : LD50 (Rat): &gt; 5,000 mg/kg

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 12/2/2019

SDS Number: R0172415

Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD  
MOTOR OIL

Version: 1.0

3088

Acute inhalation toxicity : LC50 (Rat): > 3,800 mg/m<sup>3</sup>  
Exposure time: 4 h  
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks: May cause skin irritation and/or dermatitis.

**Components:**

Distillates, petroleum, solvent-refined heavy paraffinic:

Species: Rabbit

Result: No skin irritation

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Irritating to skin.

Naphtha (petroleum), heavy aromatic:

Result: Slight, transient irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:**

Distillates, petroleum, solvent-refined heavy paraffinic:

Species: Rabbit

Result: No eye irritation

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

**Components:**

Distillates, petroleum, solvent-refined heavy paraffinic:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Genotoxicity in vitro : Test Type: Ames test

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 12/2/2019

SDS Number: R0172415

Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD  
MOTOR OIL

Version: 1.0

3088

Result: negative

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Components:**Distillates, petroleum, solvent-refined heavy paraffinic:  
No aspiration toxicity classification

Naphtha (petroleum), heavy aromatic:

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks: No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Components:**

Distillates, petroleum, solvent-refined heavy paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubilityToxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): &gt;=

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 12/2/2019

SDS Number: R0172415

Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD  
MOTOR OIL

Version: 1.0

3088

100 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l  
Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: WAF  
Method: OECD Test Guideline 211

**Persistence and degradability****Components:**

Distillates, petroleum, solvent-refined heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 2 - 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Biodegradability : Result: Inherently biodegradable.  
Biodegradation: 58.6 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

No data available

**Bioaccumulative potential****Components:**

No data available

**Mobility in soil****Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**Components:**

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**



**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 12/2/2019

SDS Number: R0172415

Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD  
MOTOR OIL

Version: 1.0

3088

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods

**CFR\_RAIL\_C**

Not dangerous goods

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**TDG\_ROAD\_C**

Not dangerous goods

**TDG\_RAIL\_C**

Not dangerous goods

**TDG\_INWT\_C**

Not dangerous goods



**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 12/2/2019

SDS Number: R0172415

Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD  
MOTOR OIL

Version: 1.0

3088

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MX\_DG**

Not dangerous goods

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.


**SECTION 15. REGULATORY INFORMATION**

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

**The components of this product are reported in the following inventories:**

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

**Inventories**


		Page: 14
<b>SAFETY DATA SHEET</b>		Revision Date: 05/19/2017
		Print Date: 12/2/2019
		SDS Number: R0172415
Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD MOTOR OIL		Version: 1.0
3088		

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

## SECTION 16. OTHER INFORMATION

### Further information

Revision Date: 05/19/2017

<p><b>NFPA:</b></p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health      Instability</p> <p>Special hazard.</p> </div>	<p><b>HMIS III:</b></p> <table border="1" style="width: 100%; text-align: center;"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="font-size: 24pt;"><b>2</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="font-size: 24pt;"><b>2</b></td> </tr> <tr> <td style="background-color: yellow; color: black;"><b>PHYSICAL HAZARD</b></td> <td style="font-size: 24pt;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>2</b>	<b>FLAMMABILITY</b>	<b>2</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>2</b>						
<b>FLAMMABILITY</b>	<b>2</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIA

### Full text of H-Statements


H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

		Page: 15
<b>SAFETY DATA SHEET</b>		Revision Date: 05/19/2017
		Print Date: 12/2/2019
		SDS Number: R0172415
Valvoline™ MP 2 CYCLE TC-W3 OUTBOARD MOTOR OIL		Version: 1.0
3088		

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
 BEI : Biological Exposure Index  
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
 FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System