		Page: 1
SAFETY DATA SHEET		Revision Date: 06/12/2019
		Print Date: 12/2/2019
		SDS Number: R0289372
Valvoline™ Durablend™ SAE 10W-30 Motor Oil 3469		Version: 1.2

GHS classification in accordance with the Hazardous Products Regulations

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ Durablend™ SAE 10W-30 Motor Oil

<p>Details of the supplier of the safety data sheet Valvoline Canada Corp 905 Winston Churchill Blvd Mississauga ON L5J 4P2 Canada 1-800-TEAMVAL (1-800-832-6825)</p> <p>SDS@valvoline.com</p>	<p>Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)</p> <p>Product Information 1-800-TEAMVAL (1-800-832-6825)</p>
--	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	>=50.00 - < 70.00
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	Not a hazardous substance or mixture.	>=10.00 - < 20.00
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	>=5.00 - < 10.00

**SAFETY DATA SHEET**

Revision Date: 06/12/2019

Print Date: 12/2/2019

SDS Number: R0289372

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.2

3469

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
Nitrogen oxides (NO_x)
- Specific extinguishing methods :



SAFETY DATA SHEET	Revision Date: 06/12/2019
	Print Date: 12/2/2019
	SDS Number: R0289372
Valvoline™ Durablend™ SAE 10W-30 Motor Oil 3469	Version: 1.2

Product is compatible with standard fire-fighting agents.

- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
- Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3	CA QC OEL



SAFETY DATA SHEET	Revision Date: 06/12/2019
	Print Date: 12/2/2019
	SDS Number: R0289372
Valvoline™ Durablend™ SAE 10W-30 Motor Oil 3469	Version: 1.2

			Mist	
		TWA	1 mg/m3 Mist	CA BC OEL
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	0.2 mg/m3 Mist	CA BC OEL
		TWA	1 mg/m3 Mist	CA BC OEL
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	1 mg/m3 Mist	CA BC OEL

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Safety shoes
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

**SAFETY DATA SHEET**

Revision Date: 06/12/2019

Print Date: 12/2/2019

SDS Number: R0289372

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.2

3469

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	amber
Odour	:	No data available
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	> 425 °C
Flash point	:	> 199 °C
		Method: Cleveland open cup
Evaporation rate	:	< 1 Ethyl Ether
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	6 %(V) Calculated Explosive Limit
Lower explosion limit / Lower flammability limit	:	1 %(V) Calculated Explosive Limit
Vapour pressure	:	0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	0.870 (20 °C)
Density	:	0.8678 g/cm ³ (15.56 °C)
Solubility(ies)		
Water solubility	:	negligible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available

**SAFETY DATA SHEET**

Revision Date: 06/12/2019

Print Date: 12/2/2019

SDS Number: R0289372

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.2

3469

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : < 3,400.000 mPa.s (-20 °C)

Viscosity, kinematic : > 20.5 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Distillates, petroleum, solvent-refined heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation

**SAFETY DATA SHEET**

Revision Date: 06/12/2019

Print Date: 12/2/2019

SDS Number: R0289372

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.2

3469

under GHS.

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation

Result : Slight, transient irritation

Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit

Result : No skin irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Assessment : Slight, transient irritation

Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Unlikely to cause eye irritation or injury.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation

Assessment : No eye irritation

Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit

Result : No eye irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Result : No eye irritation


Assessment : No eye irritation

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

		Page: 8
SAFETY DATA SHEET		Revision Date: 06/12/2019
		Print Date: 12/2/2019
		SDS Number: R0289372
Valvoline™ Durablend™ SAE 10W-30 Motor Oil		Version: 1.2
3469		

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Test Type : Buehler Test
 Species : Guinea pig
 Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
 Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

Distillates, petroleum, solvent-refined heavy paraffinic:

No aspiration toxicity classification

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

**SAFETY DATA SHEET**

Revision Date: 06/12/2019

Print Date: 12/2/2019

SDS Number: R0289372

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.2

3469

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 hToxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l
aquatic invertebrates Exposure time: 48 hToxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 hToxicity to fish (Chronic : NOEC (Fish): 10 mg/l
toxicity)Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l
aquatic invertebrates
(Chronic toxicity)Ecotoxicology Assessment
Short-term (acute) aquatic : Not classified based on available information.
hazardLong-term (chronic) aquatic : Not classified based on available information.
hazard

Distillates, petroleum, solvent-refined heavy paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubilityToxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
aquatic invertebrates Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 201Toxicity to fish (Chronic : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l
toxicity) Exposure time: 14 d

**SAFETY DATA SHEET**

Revision Date: 06/12/2019

Print Date: 12/2/2019

SDS Number: R0289372

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.2

3469

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
Exposure time: 21 d
Test substance: WAF
Method: OECD Test Guideline 211

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:
Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Persistence and degradability**Components:**

Distillates, petroleum, solvent-refined heavy paraffinic:
Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:
Partition coefficient: n-octanol/water : log Pow: Expected > 7

No data available

Mobility in soil**Components:**

No data available

**SAFETY DATA SHEET**

Revision Date: 06/12/2019

Print Date: 12/2/2019

SDS Number: R0289372

Valvoline™ Durablend™ SAE 10W-30 Motor Oil

Version: 1.2

3469

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**TDG**

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

Canadian PBT Chemicals : This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA:
Zinc O,O',O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)



SAFETY DATA SHEET	Revision Date: 06/12/2019
	Print Date: 12/2/2019
	SDS Number: R0289372
Valvoline™ Durablend™ SAE 10W-30 Motor Oil 3469	Version: 1.2

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : Not in compliance with the inventory
- ENCS : Contact your sales representative for additional information.
- KECI : On the inventory, or in compliance with the inventory
- IECSC : q (quantity restricted)
- PICCS : Not in compliance with the inventory
- TCSI : Not in compliance with the inventory
- TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)


SECTION 16. OTHER INFORMATION

Further information

Revision Date: 06/12/2019

<p>NFPA:</p> <p style="text-align: center;">Special hazard.</p>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	0	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	0						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB

	Page: 14
SAFETY DATA SHEET	Revision Date: 06/12/2019
	Print Date: 12/2/2019
	SDS Number: R0289372
Valvoline™ Durablend™ SAE 10W-30 Motor Oil 3469	Version: 1.2

vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System