		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 03/29/2019
		Print Date: 12/2/2019
		SDS Number: R0296766
ZEREX™ G05® Antifreeze Coolant		Version: 1.1
3477		

GHS classification in accordance with the Hazardous Products Regulations

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier**

Trade name : ZEREX™ G05®  
Antifreeze Coolant

<p><b>Details of the supplier of the safety data sheet</b> Valvoline Canada Corp 905 Winston Churchill Blvd Mississauga ON L5J 4P2 Canada 1-800-TEAMVAL (1-800-832-6825)</p> <p>SDS@valvoline.com</p>	<p><b>Emergency telephone number</b> 1-800-VALVOLINE (1-800-825-8654)</p> <p><b>Regulatory Information Number</b> 1-800-TEAMVAL (1-800-832-6825)</p> <p><b>Product Information</b> 1-800-TEAMVAL (1-800-832-6825)</p>
---	---

**SECTION 2. HAZARDS IDENTIFICATION**


**GHS Classification**

Acute toxicity (Oral) : Category 4

Reproductive toxicity : Category 1B

Specific target organ toxicity - repeated exposure (Oral) : Category 2 (Kidney, Liver)

**GHS label elements**

Hazard pictograms :  

Signal word : Danger

Hazard statements : H302 Harmful if swallowed.  
H360 May damage fertility or the unborn child.  
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	>=90.00 - <= 100.00
DIETHYLENE GLYCOL	111-46-6	Acute Tox. 4; H302 STOT RE 2; H373	>=1.00 - < 5.00
SODIUM BENZOATE	532-32-1	Eye Irrit. 2A; H319	>=1.00 - < 5.00
DISODIUM TETRABORATE	1330-43-4	Repr. 1B; H360	>=1.00 - < 5.00
SODIUM NITRITE	7632-00-0	Ox. Sol. 2; H272 Acute Tox. 3; H301 Eye Irrit. 2A; H319	>=0.10 - < 1.00



<b>SAFETY DATA SHEET</b>	Revision Date: 03/29/2019
	Print Date: 12/2/2019
	SDS Number: R0296766
ZEREX™ G05® Antifreeze Coolant 3477	Version: 1.1

--	--	--	--

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.  
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
stomach or intestinal upset (nausea, vomiting, diarrhea)



<b>SAFETY DATA SHEET</b>	Revision Date: 03/29/2019
	Print Date: 12/2/2019
	SDS Number: R0296766
ZEREX™ G05® Antifreeze Coolant	Version: 1.1
3477	

irritation (nose, throat, airways)  
 Cough  
 pain in the abdomen and lower back  
 cyanosis (causes blue coloring of the skin and nails from lack of oxygen)  
 lung edema (fluid buildup in the lung tissue)  
 acute kidney failure (sudden slowing or stopping of urine production)  
 Convulsions  
 Harmful if swallowed.  
 May damage fertility or the unborn child.  
 May cause damage to organs through prolonged or repeated exposure if swallowed.

Notes to physician

: This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 Water spray  
 Foam  
 Carbon dioxide (CO2)  
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Alcohols  
 Aldehydes  
 carbon dioxide and carbon monoxide  
 ethers  
 toxic fumes  
 Hydrocarbons



<b>SAFETY DATA SHEET</b>	Revision Date: 03/29/2019
	Print Date: 12/2/2019
	SDS Number: R0296766
ZEREX™ G05® Antifreeze Coolant 3477	Version: 1.1

Sodium oxides

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours/dust.  
Do not smoke.  
Container hazardous when empty.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national



<b>SAFETY DATA SHEET</b>	Revision Date: 03/29/2019
	Print Date: 12/2/2019
	SDS Number: R0296766
ZEREX™ G05® Antifreeze Coolant 3477	Version: 1.1

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	(c)	100 mg/m3	CA AB OEL
		TWA	10 mg/m3 particulate	CA BC OEL
		STEL	20 mg/m3 particulate	CA BC OEL
		C	100 mg/m3 aerosol	CA BC OEL
		C	50 ppm Vapour	CA BC OEL
		C	50 ppm 127 mg/m3 Vapour and mist	CA QC OEL
DISODIUM TETRABORATE	1330-43-4	TWA	1 mg/m3	CA AB OEL
		STEL	3 ppm	CA AB OEL
		TWAEV	1 mg/m3	CA QC OEL
		TWA	2 mg/m3 Inhalable (Borate)	CA BC OEL
		STEL	6 mg/m3 Inhalable (Borate)	CA BC OEL

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

In the case of vapour formation use a respirator with an approved filter.

- Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:  
Impervious clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Colour : light yellow
- Odour : mild
- Odour Threshold : No data available
- pH : Average 6.5
- Melting point/freezing point : No data available
- Boiling point/boiling range : 330 °F  
(1013 hPa)
- Flash point : > 121.1 °C

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

Method: closed cup

Evaporation rate	:	> 1 Ethyl Ether
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	15.3 %(V)
Lower explosion limit / Lower flammability limit	:	3.2 %(V)
Vapour pressure	:	1.1 mmHg (20 °C)
Relative vapour density	:	> 1 AIR=1
Relative density	:	No data available
Density	:	Average 1.1362 g/cm <sup>3</sup> (15.56 °C)
Solubility(ies)	:	
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous reactions	:	Product will not undergo hazardous polymerization.

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

Conditions to avoid : excessive heat  
Exposure to moisture

Incompatible materials : Acids  
Aldehydes  
Alkali metals  
Alkaline earth metals  
Bases  
iron salts  
strong alkalis  
Strong oxidizing agents  
Sulphur compounds

Hazardous decomposition products : Alcohols  
Aldehydes  
carbon dioxide and carbon monoxide  
ethers  
Hydrocarbons  
Organic acids  
Sodium oxides  
toxic fumes  
ketones

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Eye Contact  
Ingestion

**Acute toxicity**

Harmful if swallowed.

**Product:**

Acute oral toxicity : Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be considered toxic by ingestion.

Acute toxicity estimate: 512.68 mg/kg  
Method: Calculation method

Acute dermal toxicity : Remarks: Skin absorption of this material (or a component) may be increased through injured skin.

**Components:****ETHYLENE GLYCOL:**

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

Acute oral toxicity : LD0 (Human): estimated 1.56 g/kg

Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l  
Exposure time: 1 h  
Test atmosphere: dust/mist  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

Acute toxicity (other routes of administration) : LD50 (Rat): 5,010 mg/kg  
Application Route: Intraperitoneal

LD50 (Rat): 3,260 mg/kg  
Application Route: Intravenous

**DIETHYLENE GLYCOL:**

Acute oral toxicity : LD50 (Human): Expected 1,120 mg/kg  
Target Organs: Kidney

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

**SODIUM BENZOATE:**

Acute oral toxicity : LD50 (Rat, male and female): 3,450 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 12.2 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Remarks: Information given is based on data obtained from similar substances.

**DISODIUM TETRABORATE:**

Acute inhalation toxicity : LC50 (Rat): > 2.03 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: No adverse effect has been observed in acute

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

dermal toxicity tests.

**SODIUM NITRITE:**

Acute oral toxicity : LD50 (Rat): 180 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist**Skin corrosion/irritation**

Not classified based on available information.

**Components:****ETHYLENE GLYCOL:**Species : Rabbit  
Result : No skin irritation**DIETHYLENE GLYCOL:**Species : Human  
Result : Slight, transient irritation**SODIUM BENZOATE:**Assessment : Slight, transient irritation  
Result : Slight, transient irritation**DISODIUM TETRABORATE:**Species : Rabbit  
Result : No skin irritation**SODIUM NITRITE:**Assessment : No skin irritation  
Result : No skin irritation**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : Unlikely to cause eye irritation or injury.

**Components:****ETHYLENE GLYCOL:**

Result : Slight, transient irritation

**DIETHYLENE GLYCOL:**Species : Rabbit  
Result : Slight, transient irritation**SODIUM BENZOATE:**Species : Rabbit  
Result : Irritating to eyes.  
Method : OECD Test Guideline 405

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

**DISODIUM TETRABORATE:**

Result : Slight, transient irritation

**SODIUM NITRITE:**

Result : Irritating to eyes.

Assessment : Irritating to eyes.

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:****ETHYLENE GLYCOL:**

Test Type : Maximisation Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.

**DIETHYLENE GLYCOL:**

Test Type : Maximisation Test  
Species : Guinea pig  
Method : Directive 67/548/EEC, Annex V, B.6.  
Result : Did not cause sensitisation on laboratory animals.

**DISODIUM TETRABORATE:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****ETHYLENE GLYCOL:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Result: negative

**DIETHYLENE GLYCOL:**

Genotoxicity in vitro : Test Type: Ames test  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative  
GLP: yes  
  
Test system: Chinese hamster ovary cells  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 479  
Result: negative

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test  
Species: Mouse  
Method: OECD Test Guideline 474  
Result: negative  
GLP: yes

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

May damage fertility or the unborn child.

**Components:****DISODIUM TETRABORATE:**

Reproductive toxicity - : Clear evidence of adverse effects on sexual function and  
Assessment : fertility, and/or on development, based on animal experiments

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

**Components:****ETHYLENE GLYCOL:**

Exposure routes : Ingestion  
Target Organs : Kidney, Liver  
Assessment : May cause damage to organs through prolonged or repeated exposure.

**DIETHYLENE GLYCOL:**

Exposure routes : Ingestion  
Target Organs : Kidney  
Assessment : May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Experience with human exposure****Components:****ETHYLENE GLYCOL:**

Ingestion : Target Organs: Kidney

**DIETHYLENE GLYCOL:**

General Information : Liver  
Kidney

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

**Further information****Product:**

Remarks : No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Not classified based on available information.

**Components:****ETHYLENE GLYCOL:**Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l  
Exposure time: 96 h  
Test Type: static testLC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l  
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static testToxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l  
End point: Growth inhibition  
Exposure time: 7 DaysToxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l  
Exposure time: 7 dToxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l  
Exposure time: 7 d**DIETHYLENE GLYCOL:**Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 24 h  
Test Type: static test  
Method: DIN 38412**SODIUM BENZOATE:**Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

Test Type: static test  
Method: Static  
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: Static  
Remarks: Mortality

**DISODIUM TETRABORATE:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 79.7 mg/l  
Exposure time: 96 h  
Remarks: Information refers to the main component.

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 17.5 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
Remarks: Information refers to the main component.

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): 5.6 mg/l  
Exposure time: 34 d  
Test Type: semi-static test  
Method: OECD Test Guideline 210  
Remarks: Information refers to the main component.

**SODIUM NITRITE:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.35 - 3.81 mg/l  
Exposure time: 96 h  
Test Type: flow-through test

LC50 (Oncorhynchus mykiss (rainbow trout)): 0.54 - 26.3 mg/l  
Exposure time: 96 h  
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 15.4 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic) : NOEC (Ictalurus catus (catfish)): 6.16 mg/l

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

toxicity)

Exposure time: 31 d  
Test Type: flow-through testToxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 9.86 mg/l  
Exposure time: 80 d  
Test Type: static testToxicity to bacteria : EC10 (activated sludge): 210 mg/l  
Exposure time: 3 h  
Test Type: Static  
Method: OECD Test Guideline 209**Persistence and degradability****Components:****ETHYLENE GLYCOL:**Biodegradability : Result: Readily biodegradable.  
Biodegradation: 90 - 100 %  
Exposure time: 10 d  
Method: OECD Test Guideline 301**DIETHYLENE GLYCOL:**Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70 - 80 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B**SODIUM BENZOATE:**Biodegradability : Result: Readily biodegradable.  
Biodegradation: 88 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301**DISODIUM TETRABORATE:**

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

**SODIUM NITRITE:**

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

No data available

**Bioaccumulative potential****Components:****ETHYLENE GLYCOL:**Bioaccumulation : Species: Crayfish (Procambarus)  
Bioconcentration factor (BCF): 0.27  
Exposure time: 61 d  
Concentration: 1000 mg/l  
Method: Flow through

**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

Partition coefficient: n-octanol/water : log Pow: -1.36

DIETHYLENE GLYCOL:  
Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
Bioconcentration factor (BCF): 100

Partition coefficient: n-octanol/water : log Pow: -1.47

SODIUM NITRITE:  
Partition coefficient: n-octanol/water : log Pow: -3.700 (25 °C)

No data available

**Mobility in soil****Components:**

SODIUM NITRITE:

Stability in soil : Remarks: Not expected to adsorb on soil.

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life.

**Components:**

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

General advice : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.

---

**SECTION 14. TRANSPORT INFORMATION**



**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

**U.S. DOT - ROAD**

Not dangerous goods
---------------------

**CFR\_RAIL\_C**

Not dangerous goods
---------------------

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods
---------------------

**TDG\_ROAD\_C**

Not dangerous goods
---------------------

**TDG\_RAIL\_C**

Not dangerous goods
---------------------

**TDG\_INWT\_C**

Not dangerous goods
---------------------

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods
---------------------

**MX\_DG**

Not dangerous goods
---------------------

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID



<b>SAFETY DATA SHEET</b>	Revision Date: 03/29/2019
	Print Date: 12/2/2019
	SDS Number: R0296766
ZEREX™ G05® Antifreeze Coolant 3477	Version: 1.1

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**The components of this product are reported in the following inventories:**

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : Not in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 03/29/2019

<b>NFPA:</b>	<b>HMIS III:</b>
--------------	------------------



**SAFETY DATA SHEET**

Revision Date: 03/29/2019

Print Date: 12/2/2019

SDS Number: R0296766

ZEREX™ G05® Antifreeze Coolant

Version: 1.1

3477

<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>1*</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>1*</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>1*</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**  
Combustible Liquid Class IIIB

**Full text of H-Statements**


- H272 May intensify fire; oxidizer.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H319 Causes serious eye irritation.
- H360 May damage fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

Sources of key data used to compile the Safety Data Sheet  
Valvoline internal data including own and sponsored test reports  
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

- ACGIH : American Conference of Industrial Hygienists
- BEI : Biological Exposure Index
- CAS : Chemical Abstracts Service (Division of the American Chemical Society).
- CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
- FG : Food grade

		Page: 21
<b>SAFETY DATA SHEET</b>		Revision Date: 03/29/2019
		Print Date: 12/2/2019
		SDS Number: R0296766
ZEREX™ G05® Antifreeze Coolant		Version: 1.1
3477		

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System