		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 10/14/2019
		Print Date: 12/3/2019
		SDS Number: R0171982
Valvoline™ SAE 20W50 Motor Oil 822592		Version: 1.6

GHS classification in accordance with the Hazardous Products Regulations

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier**

Trade name : Valvoline™ SAE 20W50 Motor Oil

<p><b>Details of the supplier of the safety data sheet</b>  Valvoline Canada Corp  905 Winston Churchill Blvd  Mississauga ON L5J 4P2  Canada  1-800-TEAMVAL (1-800-832-6825)</p> <p>SDS@valvoline.com</p>	<p><b>Emergency telephone number</b>  1-800-VALVOLINE (1-800-825-8654)</p> <p><b>Regulatory Information Number</b>  1-800-TEAMVAL (1-800-832-6825)</p> <p><b>Product Information</b>  1-800-TEAMVAL (1-800-832-6825)</p>
--	--

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	>=70.00 - < 90.00
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		Not a hazardous substance or mixture.	>=1.00 - < 5.00



<b>SAFETY DATA SHEET</b>	Revision Date: 10/14/2019
	Print Date: 12/3/2019
	SDS Number: R0171982
Valvoline™ SAE 20W50 Motor Oil 822592	Version: 1.6

Lubricating oils (petroleum), hydrotreated	64742-58-1	Not a hazardous substance or mixture.	>=1.00 - < 5.00
---	------------	--	-----------------

**SECTION 4. FIRST AID MEASURES**

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO2)  
Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons
- Specific extinguishing methods :



<b>SAFETY DATA SHEET</b>	Revision Date: 10/14/2019
	Print Date: 12/3/2019
	SDS Number: R0171982
Valvoline™ SAE 20W50 Motor Oil 822592	Version: 1.6

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL



<b>SAFETY DATA SHEET</b>	Revision Date: 10/14/2019
	Print Date: 12/3/2019
	SDS Number: R0171982
Valvoline™ SAE 20W50 Motor Oil 822592	Version: 1.6

		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	1 mg/m3 Mist	CA BC OEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
		TWA	1 mg/m3 Mist	CA BC OEL
Lubricating oils (petroleum), hydrotreated	64742-58-1	TWA	1 mg/m3 Mist	CA BC OEL

**Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:  
Safety shoes  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Colour : amber
- Odour : hydrocarbon-like

**SAFETY DATA SHEET**

Revision Date: 10/14/2019

Print Date: 12/3/2019

SDS Number: R0171982

Valvoline™ SAE 20W50 Motor Oil

Version: 1.6

822592

Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	201 - 249 °C
		Method: Cleveland open cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	6 %(V) Calculated Explosive Limit
Lower explosion limit / Lower flammability limit	:	1 %(V) Calculated Explosive Limit
Vapour pressure	:	0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	0.883 (15.56 °C)
Density	:	7.32 lb/gal
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	171 mm <sup>2</sup> /s ( 40 °C)

**SAFETY DATA SHEET**

Revision Date: 10/14/2019

Print Date: 12/3/2019

SDS Number: R0171982

Valvoline™ SAE 20W50 Motor Oil

Version: 1.6

822592

Oxidizing properties : No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation

Skin contact

Eye Contact

Ingestion

**Acute toxicity**

Not classified based on available information.

**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): &gt; 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): &gt; 5 g/kg

**Lubricating oils (petroleum), hydrotreated:**Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by ingestion under GHS.Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.**Skin corrosion/irritation**

Not classified based on available information.

**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation

**SAFETY DATA SHEET**

Revision Date: 10/14/2019

Print Date: 12/3/2019

SDS Number: R0171982

Valvoline™ SAE 20W50 Motor Oil

Version: 1.6

822592

Result : Slight, transient irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation

Result : Slight, transient irritation

**Lubricating oils (petroleum), hydrotreated:**

Assessment : No skin irritation

Result : No skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : Unlikely to cause eye irritation or injury.

**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation

Assessment : No eye irritation

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : Slight, transient irritation

Assessment : Slight, transient irritation

**Lubricating oils (petroleum), hydrotreated:**

Result : Slight, transient irritation

Assessment : Slight, transient irritation

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**Reproductive toxicity**

Not classified based on available information.

**SAFETY DATA SHEET**

Revision Date: 10/14/2019

Print Date: 12/3/2019

SDS Number: R0171982

Valvoline™ SAE 20W50 Motor Oil

Version: 1.6

822592

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

No aspiration toxicity classification

**Further information****Product:**

Remarks : No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.


Long-term (chronic) aquatic hazard : Not classified based on available information.

**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
Exposure time: 48 hToxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment Short-term (acute) aquatic : Not classified based on available information.

		Page: 9
<b>SAFETY DATA SHEET</b>		Revision Date: 10/14/2019
		Print Date: 12/3/2019
		SDS Number: R0171982
Valvoline™ SAE 20W50 Motor Oil		Version: 1.6
822592		

hazard

Long-term (chronic) aquatic hazard : Not classified based on available information.

Lubricating oils (petroleum), hydrotreated:

Toxicity to daphnia and other aquatic invertebrates : LC50 (Brine shrimp (*Artemia salina*)): > 22,500 mg/l  
Exposure time: 48 h

Ecotoxicology Assessment

Short-term (acute) aquatic hazard :

Not classified based on available information.

Long-term (chronic) aquatic hazard : No toxicity at the limit of solubility

Not classified based on available information.

**Persistence and degradability**

**Components:**

No data available

**Bioaccumulative potential**

**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-octanol/water : log Pow: Expected > 7

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**Components:**


---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

		Page: 10
<b>SAFETY DATA SHEET</b>		Revision Date: 10/14/2019
		Print Date: 12/3/2019
		SDS Number: R0171982
Valvoline™ SAE 20W50 Motor Oil		Version: 1.6
822592		

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### TDG

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

## SECTION 15. REGULATORY INFORMATION

**Canadian PBT Chemicals** : This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)

**The components of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory



# SAFETY DATA SHEET

Revision Date: 10/14/2019

Print Date: 12/3/2019

SDS Number: R0171982

Valvoline™ SAE 20W50 Motor Oil

Version: 1.6

822592

### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

## SECTION 16. OTHER INFORMATION

### Further information

Revision Date: 10/14/2019

<p><b>NFPA:</b></p> <p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<p><b>HMIS III:</b></p> <table border="1"> <tr> <td><b>HEALTH</b></td> <td><b>0</b></td> </tr> <tr> <td><b>FLAMMABILITY</b></td> <td><b>1</b></td> </tr> <tr> <td><b>PHYSICAL HAZARD</b></td> <td><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>0</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>0</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

### NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class III B


### Full text of H-Statements

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

		Page: 12
<b>SAFETY DATA SHEET</b>		Revision Date: 10/14/2019
		Print Date: 12/3/2019
		SDS Number: R0171982
Valvoline™ SAE 20W50 Motor Oil		Version: 1.6
822592		

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System