		Page: 1
SAFETY DATA SHEET		Revision Date: 05/22/2017
		Print Date: 12/3/2019
		SDS Number: R0321370
ZEREX™ G05® Antifreeze Coolant		Version: 1.0
857780		

GHS classification in accordance with the Hazardous Products Regulations

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : ZEREX™ G05®
Antifreeze Coolant


<p>Details of the supplier of the safety data sheet Valvoline Canada Corp 905 Winston Churchill Blvd Mississauga ON L5J 4P2 Canada 1-800-TEAMVAL</p>	<p>Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL</p> <p>Product Information 1-800-TEAMVAL</p>
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4
Reproductive toxicity : Category 1B
Specific target organ toxicity - repeated exposure (Oral) : Category 2 (Kidney, Liver)

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H302 Harmful if swallowed.
H360 May damage fertility or the unborn child.
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ protective clothing/ eye protection/
face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON
CENTER/doctor if you feel unwell. Rinse mouth.

P308 + P313 IF exposed or concerned: Get medical advice/
attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste
disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	>=50.00 - < 70.00
DIETHYLENE GLYCOL	111-46-6	Acute Tox. 4; H302 STOT RE 2; H373	>=1.00 - < 5.00
SODIUM BENZOATE	532-32-1	Eye Irrit. 2A; H319	>=1.00 - < 5.00
DISODIUM TETRABORATE ANHYDROUS	1330-43-4	Repr. 1B; H360	>=0.10 - < 1.00

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019


SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Cough
pain in the abdomen and lower back
cyanosis (causes blue coloring of the skin and nails from lack of oxygen)
lung edema (fluid buildup in the lung tissue)
acute kidney failure (sudden slowing or stopping of urine production)
Convulsions

		Page: 4
	SAFETY DATA SHEET	Revision Date: 05/22/2017
		Print Date: 12/3/2019
		SDS Number: R0321370
ZEREX™ G05® Antifreeze Coolant		Version: 1.0
857780		

Harmful if swallowed.
 May damage fertility or the unborn child.

Notes to physician : This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Alcohols
 Aldehydes
 carbon dioxide and carbon monoxide
 ethers
 toxic fumes
 Hydrocarbons
 Sodium oxides
- Specific extinguishing methods :

 Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.



SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 12/3/2019
	SDS Number: R0321370
ZEREX™ G05® Antifreeze Coolant 857780	Version: 1.0

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust. Do not smoke. Container hazardous when empty. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place. Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible	Basis



SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 12/3/2019
	SDS Number: R0321370
ZEREX™ G05® Antifreeze Coolant	Version: 1.0
857780	

			concentration	
ETHYLENE GLYCOL	107-21-1	(c)	100 mg/m3	CA AB OEL
		TWA	10 mg/m3 particulate	CA BC OEL
		STEL	20 mg/m3 particulate	CA BC OEL
		C	100 mg/m3 aerosol	CA BC OEL
		C	50 ppm Vapour	CA BC OEL
		C	50 ppm 127 mg/m3 Vapour and mist	CA QC OEL
DISODIUM TETRABORATE ANHYDROUS	1330-43-4	TWA	1 mg/m3	CA AB OEL
		STEL	3 ppm	CA AB OEL
		TWAEV	1 mg/m3	CA QC OEL
		TWA	2 mg/m3 Inhalable (Borate)	CA BC OEL
		STEL	6 mg/m3 Inhalable (Borate)	CA BC OEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

into eyes.

- Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Colour : light yellow
- Odour : No data available
- Odour Threshold : No data available
- pH : Average 8.0
- Melting point/freezing point : No data available
- Boiling point/boiling range : 225 °F / 107 °C
(1013.3 hPa)
- Flash point : > 250.0 °F / > 121.1 °C
Method: Cleveland open cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : 15.3 %(V)
- Lower explosion limit : 1.7 %(V)
- Vapour pressure : 1.800 mmHg (68.00 °F)
- Relative vapour density : > 1.000AIR=1
- Relative density : No data available

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

Density : 1.0779 g/cm³ (15.56 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat
Exposure to moistureIncompatible materials : Acids
Aldehydes
Alkali metals
Alkaline earth metals
Bases
iron salts
strong alkalis
Strong oxidizing agents
Sulphur compoundsHazardous decomposition products : Alcohols
Aldehydes
carbon dioxide and carbon monoxide
ethers
Hydrocarbons

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

Organic acids
Sodium oxides
ketones

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity :

Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in humans. Products containing diethylene glycol should be considered toxic by ingestion.

Acute dermal toxicity :

Remarks: Skin absorption of this material (or a component) may be increased through injured skin.

Components:

ETHYLENE GLYCOL:

Acute oral toxicity :

LD0 (Human): Estimated 1.56 g/kg

Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity :

LC50 (Rat): 10.9 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity :

LD50 (Rabbit): 9,530 mg/kg

DIETHYLENE GLYCOL:

Acute oral toxicity :

LD50 (Human): Expected 1,120 mg/kg

Target Organs: Kidney

Acute inhalation toxicity :

LC50 (Rat): > 4.6 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: No adverse effect has been observed in acute

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

SODIUM BENZOATE:

Acute oral toxicity : LD50 (Rat, male and female): 3,450 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 12.2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Remarks: Information given is based on data obtained from similar substances.

DISODIUM TETRABORATE ANHYDROUS:

Acute inhalation toxicity : LC50 (Rat): > 2.03 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Components:**ETHYLENE GLYCOL:**

Species: Rabbit

Result: No skin irritation

DIETHYLENE GLYCOL:

Species: Human

Result: Slight, transient irritation

SODIUM BENZOATE:

Result: Slight, transient irritation

DISODIUM TETRABORATE ANHYDROUS:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

Components:

ETHYLENE GLYCOL:

Result: Slight, transient irritation

DIETHYLENE GLYCOL:

Species: Rabbit

Result: Slight, transient irritation

SODIUM BENZOATE:

Species: Rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

DISODIUM TETRABORATE ANHYDROUS:

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

DIETHYLENE GLYCOL:

Test Type: Maximisation Test

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Did not cause sensitisation on laboratory animals.

DISODIUM TETRABORATE ANHYDROUS:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Genotoxicity in vitro

: Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

DIETHYLENE GLYCOL:

Genotoxicity in vitro

: Test Type: Ames test

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

: Test species: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 479

Result: negative

GLP: yes

Genotoxicity in vivo

: Test Type: In vivo micronucleus test

Test species: Mouse

Method: OECD Test Guideline 474

Result: negative

GLP: yes

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility or the unborn child.

Components:

DISODIUM TETRABORATE ANHYDROUS:

Reproductive toxicity -

: Clear evidence of adverse effects on sexual function and

Assessment

fertility, and/or on development, based on animal experiments

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney, Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

DIETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Experience with human exposure**Components:**

DIETHYLENE GLYCOL:

Liver

Further information**Product:**

Remarks: No data available

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:**ETHYLENE GLYCOL:**Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l
Exposure time: 96 h
Test Type: static testLC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static testToxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l
End point: Growth inhibition
Exposure time: 7 DaysToxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l
Exposure time: 7 dToxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l
Exposure time: 7 d**DIETHYLENE GLYCOL:**Toxicity to fish : LC50 (Fathead minnow (Pimephales promelas)): 75,210 mg/l
Exposure time: 96 h
Test Type: flow-through testToxicity to daphnia and other aquatic invertebrates : LC50 (Water flea (Daphnia magna)): > 10,000 mg/l
Exposure time: 24 h
Test Type: static test
Method: DIN 38412**SODIUM BENZOATE:**Toxicity to fish : LC50 (Fathead minnow (Pimephales promelas)): > 100 mg/l
Exposure time: 96 h
Test Type: static test

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

Method: Static
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : LC50 (Water flea (Daphnia magna)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: Static
Remarks: Mortality

DISODIUM TETRABORATE ANHYDROUS:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 79.7 mg/l
Exposure time: 96 h
Remarks: Information refers to the main component.

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 17.5 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
Remarks: Information refers to the main component.

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): 5.6 mg/l
Exposure time: 34 d
Test Type: semi-static test
Method: OECD Test Guideline 210
Remarks: Information refers to the main component.

Persistence and degradability**Components:****ETHYLENE GLYCOL:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 10 d
Method: OECD Test Guideline 301

DIETHYLENE GLYCOL:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

SODIUM BENZOATE:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 88 %
Exposure time: 28 d
Method: OECD Test Guideline 301

DISODIUM TETRABORATE ANHYDROUS:

Biodegradability : Result: The methods for determining biodegradability are not

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

applicable to inorganic substances.

No data available

Bioaccumulative potential**Components:**

ETHYLENE GLYCOL:

Bioaccumulation

: Species: Crayfish (Procambarus)
Bioconcentration factor (BCF): 0.27
Exposure time: 61 d
Concentration: 1000 mg/l
Method: Flow through

Partition coefficient: n-
octanol/water

: log Pow: -1.36

DIETHYLENE GLYCOL:

Bioaccumulation

: Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 100

Partition coefficient: n-
octanol/water

: log Pow: -1.47

No data available

Mobility in soil**Components:**

No data available

Other adverse effects

No data available

Product:Additional ecological
information

: No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

General advice

: Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and
federal regulations.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste
handling site for recycling or disposal.



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG



SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 12/3/2019
	SDS Number: R0321370
ZEREX™ G05® Antifreeze Coolant 857780	Version: 1.0

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : Not in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2017

NFPA:	HMIS III:
--------------	------------------

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0321370

ZEREX™ G05® Antifreeze Coolant

Version: 1.0

857780

<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">1*</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	1*	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	1*						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H360	May damage fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index


CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

		Page: 19
SAFETY DATA SHEET		Revision Date: 05/22/2017
		Print Date: 12/3/2019
		SDS Number: R0321370
ZEREX™ G05® Antifreeze Coolant		Version: 1.0
857780		

IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System