	Page: 1
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 12/3/2019
	SDS Number: R0257033
Valvoline™ Full Synthetic Moly Fortified Gray Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV985	Version: 1.0

GHS classification in accordance with the Hazardous Products Regulations

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ Full Synthetic Moly Fortified Gray Grease
™ Trademark, Valvoline or its subsidiaries, registered in various countries


<p>Details of the supplier of the safety data sheet Valvoline Canada Corp 905 Winston Churchill Blvd Mississauga ON L5J 4P2 Canada 1-800-TEAMVAL</p>	<p>Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL</p> <p>Product Information 1-800-TEAMVAL</p>
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A

GHS label elements

Hazard pictograms : 

Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P280 Wear eye protection/ face protection.
Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0257033

Valvoline™ Full Synthetic Moly Fortified Gray Grease
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
VV985

Version: 1.0

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
POLYETHYLENE	9002-88-4	Not a hazardous substance or mixture.	>=5.00 - < 10.00
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	Skin Irrit. 2; H315 Eye Dam. 1; H318	>=1.00 - < 3.00
MOLYBDENUM DISULFIDE	1317-33-5	Not a hazardous substance or mixture.	>=1.00 - < 5.00

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms : Signs and symptoms of exposure to this material through



SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 12/3/2019
	SDS Number: R0257033
Valvoline™ Full Synthetic Moly Fortified Gray Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV985	Version: 1.0

and effects, both acute and delayed

breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Causes serious eye irritation.

Notes to physician

: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO2)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Oxides of phosphorus

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and : Use personal protective equipment.
Persons not wearing protective equipment should be excluded



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0257033

Version: 1.0

Valvoline™ Full Synthetic Moly Fortified Gray Grease
 ™ Trademark, Valvoline or its subsidiaries,
 registered in various countries
 VV985

- emergency procedures : from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
 Do not smoke.
 Container hazardous when empty.
 Avoid contact with skin and eyes.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
POLYETHYLENE	9002-88-4	TWAEV	10 mg/m3 total dust	CA QC OEL
MOLYBDENUM DISULFIDE	1317-33-5	TWA	10 mg/m3 Total (Molybdenum)	CA AB OEL
		TWA	3 mg/m3 Respirable	CA AB OEL



SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 12/3/2019
	SDS Number: R0257033
Valvoline™ Full Synthetic Moly Fortified Gray Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV985	Version: 1.0

		(Molybdenum)	
	TWAEV	10 mg/m3 (Molybdenum)	CA QC OEL
	TWA	10 mg/m3 Inhalable (Molybdenum)	CA BC OEL
	TWA	3 mg/m3 Respirable (Molybdenum)	CA BC OEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

: Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0257033

Valvoline™ Full Synthetic Moly Fortified Gray Grease
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
VV985

Version: 1.0

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Physical state	: liquid
Colour	: dark grey
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: 500 °F / 260 °C
Boiling point/boiling range	: 700 °F / 371 °C
Flash point	: 419 °F / 215 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.919 g/cm ³ (20 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0257033

Version: 1.0

Valvoline™ Full Synthetic Moly Fortified Gray Grease
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
VV985

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : > 315 °C

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : None known.
None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : LD50 (Rat): 93,458 mg/kg
Method: Acute toxicity estimate

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0257033

Valvoline™ Full Synthetic Moly Fortified Gray Grease
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
VV985

Version: 1.0

Acute dermal toxicity : LD50 (Rabbit): 2,599 mg/kg
Method: Acute toxicity estimate

Components:

POLYETHYLENE:

Acute oral toxicity : LD50 (Rat): > 3,000 mg/kg

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Acute oral toxicity : LD50 (Rat): > 2,000 - 5,000 mg/kg
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: Information given is based on data obtained from similar substances.

MOLYBDENUM DISULFIDE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: No skin irritation

Remarks: May cause skin irritation in susceptible persons.

Components:

POLYETHYLENE:

Result: No skin irritation

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Result: Irritating to skin.

MOLYBDENUM DISULFIDE:


Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes

	Page: 9
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 12/3/2019
	SDS Number: R0257033
Valvoline™ Full Synthetic Moly Fortified Gray Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV985	Version: 1.0

serious eye irritation.

Components:

POLYETHYLENE:

Result: No eye irritation

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Result: Corrosive

MOLYBDENUM DISULFIDE:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 3; Harmful to aquatic life with long lasting effects.

Components:

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Toxicity to fish : LC50 (Fish): > 1 - 10 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from similar substances.

**SAFETY DATA SHEET**

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0257033

Valvoline™ Full Synthetic Moly Fortified Gray Grease
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
VV985

Version: 1.0

Toxicity to daphnia and other aquatic invertebrates : EC50 (Aquatic invertebrates): > 10 - 100 mg/l
Exposure time: 48 h
Remarks: Information given is based on data obtained from similar substances.

Toxicity to algae : EC50 (Green algae): > 10 - 100 mg/l
Exposure time: 72 h
Remarks: Information given is based on data obtained from similar substances.

Persistence and degradability

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Biodegradability : Biodegradation: 1.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0257033

Version: 1.0

Valvoline™ Full Synthetic Moly Fortified Gray Grease
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
VV985

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO


Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

		Page: 12
SAFETY DATA SHEET		Revision Date: 05/22/2017
		Print Date: 12/3/2019
		SDS Number: R0257033
Valvoline™ Full Synthetic Moly Fortified Gray Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV985		Version: 1.0

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The components of this product are reported in the following inventories:

- TSCA : On the inventory, or in compliance with the inventory
- DSL : This product contains the following components that are not on the Canadian DSL nor NDSL.
- AICS : Not in compliance with the inventory
- ENCS : Not in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- KECI : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2017

NFPA:	HMIS III:
--------------	------------------



SAFETY DATA SHEET

Revision Date: 05/22/2017

Print Date: 12/3/2019

SDS Number: R0257033

Valvoline™ Full Synthetic Moly Fortified Gray Grease
™ Trademark, Valvoline or its subsidiaries,
registered in various countries
VV985

Version: 1.0

<p>Flammability</p> <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr><td>HEALTH</td><td>2</td></tr> <tr><td>FLAMMABILITY</td><td>1</td></tr> <tr><td>PHYSICAL HAZARD</td><td>0</td></tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

- H315 Causes skin irritation.
- H318 Causes serious eye damage.


Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

- ACGIH : American Conference of Industrial Hygienists
- BEI : Biological Exposure Index
- CAS : Chemical Abstracts Service (Division of the American Chemical Society).
- CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
- FG : Food grade
- GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
- H-statement : Hazard Statement
- IATA : International Air Transport Association.

	Page: 14
SAFETY DATA SHEET	Revision Date: 05/22/2017
	Print Date: 12/3/2019
	SDS Number: R0257033
Valvoline™ Full Synthetic Moly Fortified Gray Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV985	Version: 1.0

IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System