



Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario, L9T 3Y5  
Canada  
905-878-4990

**PRODUCT: PF 532 PRO GUARD RUBBERIZED GRAVLGUARD BLACK**

### SECTION 01: Chemical product and company identification

Manufactured for..... Pro Form Products Ltd.  
604 McGeachie Drive  
Milton, Ontario L9T3Y5  
Tel (905) 878-4990 Fax (905) 878-1189

Product name..... PF 532 PRO GUARD RUBBERIZED GRAVLGUARD BLACK

Recommended use and restrictions on use Paints.

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.

HMIS..... H: 2 F: 4 R: 0.

24 hour emergency number:..... IN CANADA CALL CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES  
CALL CHEMTREC 1-800-424-9300. .

### SECTION 02: Hazards identification



Signal Word..... DANGER.

Hazard Classification..... Aerosol 1. Gases Under Pressure: Liquefied Gas. Aspiration Toxicity 1. Skin Irritant 2. Specific Target Organ Toxicity — Single Exposure — Category 3. (narcotic effects). Carcinogenicity — Category 1. Reproductive 2. Specific Target Organ Toxicity — Repeated Exposure — Category 2.

Hazard Description..... H222 Extremely flammable aerosol . H229 Pressurized container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H350 This product contains ingredients that may cause cancer. H361 This product contains ingredients that are suspected of damaging fertility or the unborn child. H373 May cause damage to the liver and kidneys through prolonged or repeated contact.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P251 Do not pierce or burn container, even after use. P260 Do not breathe the mist, vapours, or spray. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.

Response ..... P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P331 Do NOT induce vomiting. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P302 + P352 - If on skin: wash with plenty of water. . P362 + P364 - Take off contaminated clothing and wash before reuse. P332 + P313 - If skin irritation occurs get medical attention or advice. P321 - For specific treatment see section 4 on this SDS.

Storage..... P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50°C / 122°F. P405 Store locked up. P403 Store in a well ventilated area. P403 + P233 Store in a well ventilated area. Keep container tightly closed.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note ..... This product mixture has been classified based on its ingredients.

### SECTION 03: Composition/Information on Ingredients

HAZARDOUS INGREDIENTS	CAS #	WT. %
Dimethyl carbonate	616-38-6	15-40
Toluene	108-88-3	10-30
Hydrocarbon Resin	64742-16-1	7-13
Propane	74-98-6	7-13

**PRODUCT: PF 532 PRO GUARD RUBBERIZED GRAVLGUARD BLACK****SECTION 03: Composition/Information on Ingredients**

Isobutane	75-28-5	3-7
Solvent Naphtha, Heavy Aliphatic	64742-96-7	1-5
Crystalline Silica	14808-60-7	0.1-1
Carbon Black	1333-86-4	0.1-1

**SECTION 04: First aid measures**

Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Ingestion.....	If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, ..... whether acute or delayed	Harmful if swallowed, in contact with skin or if inhaled. Causes skin irritation. May cause eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. This product contains ingredients that may cause cancer. May damage fertility or the unborn child.
Additional information.....	Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

**SECTION 05: Fire fighting measures**

Suitable and unsuitable extinguishing media.....	Foam, "alcohol" foam, co2, dry chemical, water fog. Do not use water in a jet.
Special fire fighting procedures.....	Extremely flammable aerosol. Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Heat will cause pressure buildup and may cause explosive rupture.
Hazardous combustion products.....	Oxides of carbon (CO, CO2). Hazardous organic compounds.

**SECTION 06: Accidental release measures**

Leak/spill.....	No action shall be taken involving any personal risk or without suitable training. Evacuate all non-essential personnel. Ventilate. Eliminate all sources of ignition. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Avoid all personal contact. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations.
-----------------	---

**SECTION 07: Handling and storage**

Handling procedures.....	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking.
Storage needs.....	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight. Do not store above 50 deg C.

**PRODUCT: PF 532 PRO GUARD RUBBERIZED GRAVLGUARD BLACK****SECTION 08: Exposure controls / personal protection**

INGREDIENTS	ACGIH TLV		OSHA PEL		NIOSH
	TWA	STEL	PEL	STEL	
Dimethyl carbonate	Not established		Not established		Not established
Toluene	20 ppm	Not established	200 ppm	500 ppm 10 minutes	100 ppm / STEL 150 ppm
Hydrocarbon Resin	Not established	Not established	Not established	Not established	Not established
Propane	1,000 ppm	Not established	1,000 ppm	Not established	1,000 ppm
Isobutane	Not established	Not established	Not established	Not established	800 ppm
Solvent Naphtha, Heavy Aliphatic	Not Established	Not Established	Not Established	Not Established	Not Established
Crystalline Silica	0.025 mg/m3	Not established	0.1 mg/m3 TWA	Not established	0.05 mg/m3
Carbon Black	3.5 mg/m3	Not established	3.5 mg/m3	Not established	3.5 mg/m3

## Protective equipment

Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.
Eye/type.....	Chemical safety goggles. Chemical safety goggles and full faceshield if splash hazard exists.
Gloves/ type.....	Chemical resistant gloves.
Clothing/type.....	Wear adequate protective clothes.
Footwear/type.....	Safety boots per local regulations.
Other/type.....	Emergency showers and eye wash stations should be available.
Appropriate engineering controls.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. .

**SECTION 09: Physical and chemical properties**

Physical state.....	Aerosol.
Colour.....	Black.
Odour.....	Solvent odour.
Odour threshold (ppm).....	Not available.
Vapour pressure (mm Hg).....	50-80 psig @ 21°C.
Vapour density (air=1).....	>1.
pH.....	Not applicable.
Relative Density (Specific Gravity).....	1.01. (Aerosol). 1.12. (Liquid).
Melting / Freezing point (deg C).....	Not Available.
Solubility.....	No data.
Initial boiling point / boiling range (deg C).....	90.
Evaporation rate.....	Not available.
Flash point (deg C), method.....	-4.0. (estimate for liquid).
Auto ignition temperature (deg C).....	> 232. (liquid).
Upper flammable limit (% vol).....	12.9. (liquid).
Lower flammable limit (% vol).....	0.5. (liquid).
Coefficient of water/oil distribution.....	Not available.
VOC.....	2.49 lb/usg - 328.3 g/L.
Viscosity.....	6380 cPs, #4 @ 20 RPM. (Liquid).

**SECTION 10: Stability and reactivity**

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity .....	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Possibility of hazardous reactions.....	Hazardous polymerization will not occur.
Conditions to avoid.....	Keep away from heat. Electrostatic charge. Incompatible with strong oxidizers.
Hazardous decomposition products.....	By fire: Dense black smoke. Oxides of carbon (CO,CO2). Hydrocarbons.

**SECTION 11: Toxicological information**

**PRODUCT: PF 532 PRO GUARD RUBBERIZED GRAVLGUARD BLACK****SECTION 11: Toxicological information**

INGREDIENTS	LC50	LD50
Dimethyl carbonate	>5.36 mg/L (4 hr., rat)	>5000 mg/kg (oral, rat). >5000 mg/kg (dermal, rabbit)
Toluene	8000 ppm rat inhalation 400 ppm mouse inhalation 24hr	5,000 mg/kg rat oral; 12,124 mg/kg rabbit dermal
Hydrocarbon Resin	No Data	No Data
Propane	>1,464 mg/L 15 minutes rat	Not available
Isobutane	52 mg/L 1 hour mouse	Not available
Solvent Naphtha, Heavy Aliphatic	>6 mg/L 4 hours rat	>2,000 mg/kg oral rat >2,000 mg/kg dermal rabbit
Crystalline Silica	Not available	>22,500 mg/kg oral rat
Carbon Black	Not available	>10,000 mg/kg oral rat 3,000 mg/kg dermal rabbit

Route of exposure.....	Eye contact. Skin contact. Inhalation.
Effects of acute exposure.....	Breathing of high vapour concentrations may cause anesthetic effects and serious health effects. The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Possible damage to liver and kidneys. May cause damage to the respiratory system, lungs, eyes, skin and central nervous system. Cardiac abnormalities and reproductive organ damage. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .
Skin contact.....	Can cause severe irritation, drying, cracking, scaling, leading possibly to allergic dermatitis.
Skin absorption.....	Chronic skin exposure to solvents may cause effects similar to those identified under chronic inhalation.
Eye contact.....	Can cause redness, irritation, tissue destruction.
Ingestion.....	Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. May be harmful or fatal if swallowed.
Carcinogenicity of material.....	IARC has classified Carbon Black as "Group 2B", possibly carcinogenic to humans, based on laboratory animal inhalation studies.
Reproductive effects.....	Toluene is fetotoxic in rats and mice at maternally toxic levels. Prolonged and repeated exposure of pregnant animals (>1500 ppm) to Toluene have been reported to cause adverse fetal developmental effects.

**SECTION 12: Ecological information**

Environmental.....	Do not allow to enter waters, waste water or soil.
Persistence and degradability.....	Not available.

**SECTION 13: Disposal considerations**

Waste disposal.....	Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty.
---------------------	--

**SECTION 14: Transport information**

TDG Classification.....	UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre.
DOT Classification (Road).....	UN1950 - AEROSOLS, flammable - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons).
IATA Classification (Air).....	UN1950 - AEROSOLS, flammable - Class 2.1 - Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
IMDG Classification (Marine).....	UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity. Check IMDG regulations for limited quantity exemptions.
Marine Pollutant.....	No.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

**PRODUCT: PF 532 PRO GUARD RUBBERIZED GRAVLGUARD BLACK****SECTION 15: Regulatory information**

CEPA status.....	On Domestic Substances List (DSL).
TSCA inventory status.....	All components are listed.
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III	
Section 302 - extremely hazardous substances .....	None.
Section 311/312 - hazard categories.....	Immediate health, delayed health, fire hazard.
Section 313.....	Toluene.
EPA hazardous air pollutants (HAPS) .....	Toluene.
40CFR63	
California Proposition 65.....	*WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. *WARNING: This product contains a chemical known to the State of California to cause cancer.

**SECTION 16: Other information**

Prepared by: .....	REGULATORY AFFAIRS. Trivalent Data Systems Ltd. <a href="http://www.trivalent.com">www.trivalent.com</a> .
Telephone number:.....	(800) 387-7981.
Disclaimer:.....	DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Preparation date: .....	JAN 10/2018