



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 570 WAX BASED PERMANENT RUSTPROOING (AMBER)

SECTION 01: Chemical product and company identification

Manufactured for..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product name..... PF 570 WAX BASED PERMANENT RUSTPROOING (AMBER)

Recommended use and restrictions on use Rust proofing.

Chemical family..... Mixture.

NFPA rating..... Health: 1 Fire: 3 Reactivity: 0.

HMIS..... H: 1 F: 3 R: 0.

24 hour emergency number:..... IN CANADA CALL CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES
CALL CHEMTREC 1-800-424-9300. .

SECTION 02: Hazards identification



Signal Word..... DANGER.

Hazard Classification..... Flammable Aerosols — Category 1. Gases Under Pressure: Liquefied Gas. Eye Irritation — Category 2B. Specific Target Organ Toxicity — Repeated Exposure — Category 1.

Hazard Description..... H222 Extremely flammable aerosol . H229 Pressurized container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H320 Causes eye irritation. H372 Causes damage to organs through prolonged or repeated exposure.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P251 Do not pierce or burn container, even after use. P260 Do not breathe mist, vapours, or spray. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product.

Response P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P314 - Get medical advice/attention if you feel unwell.

Storage..... P403 Store in a well ventilated area. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50°C / 122°F.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

SECTION 03: Composition/Information on Ingredients

HAZARDOUS INGREDIENTS	CAS #	WT. %
Solvent naphtha medium aliphatic	64742-88-7	40-70
Propane	74-98-6	7-13
Isobutane	75-28-5	3-7
N-Nonane	111-84-2	1-5
Propylene carbonate	108-32-7	0.5-1.5

SECTION 04: First aid measures

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Consult a physician if irritation continues.

Skin contact..... Immediately flush skin with plenty of soap and water. Remove contaminated clothing. Wash clothing before reuse. If irritation persists, seek medical attention.

Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.

PRODUCT: PF 570 WAX BASED PERMANENT RUSTPROOING (AMBER)**SECTION 04: First aid measures**

Ingestion..... In the event of accidental ingestion, rinse mouth with water; obtain medical advice immediately. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, Causes skin irritation.
whether acute or delayed

Additional information..... Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: Fire fighting measures

Suitable and unsuitable extinguishing media..... Foam, "alcohol" foam, CO2, dry chemical, water fog. In cases of larger fires, water spray should be used. Do not use water in a jet.

Hazardous combustion products..... Oxides of carbon (CO, CO2). Other potentially toxic fumes.

Special fire fighting procedures..... Extremely flammable aerosol. Firefighters should be equipped with a breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control.

Unusual fire / explosion hazards..... Closed container may explode under extreme heat.

SECTION 06: Accidental release measures

Leak/spill..... Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Eliminate all sources of ignition. Dike area to prevent spreading. Stop leak if safe to do so. Absorb with earth, sand, or another dry inert material. Collect and contain in suitable containers. Wash area with soapy water and rinse. Collect wash water for approved disposal. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial/State, and federal regulations.

SECTION 07: Handling and storage

Handling procedures..... Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Avoid skin and eye contact. Avoid breathing vapours or mist. Keep away from heat, sparks, and open flame. Ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static, which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Handle and open container with care. Keep container closed when not in use. Employees should wash hands and face before eating or drinking.

Storage needs..... Store containers in a cool, dry and well ventilated area, out of sunlight and away from fire hazards. Keep container closed when not in use. Do not store above 50 deg C.

SECTION 08: Exposure controls / personal protection

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
Solvent naphtha medium aliphatic	Not established	Not established	Not established	Not established	Not established	Not established
Propane	1,000 ppm	Not established	1,000 ppm	Not established	1,000 ppm	1,000 ppm
Isobutane	Not established	Not established	Not established	Not established	800 ppm	800 ppm
N-Nonane	200 ppm	--	--	--	1050 mg/m3	1050 mg/m3
Propylene carbonate	Not established		Not established		Not established	Not established
Protective equipment	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.					
Respiratory/type.....	Chemical safety goggles. Chemical safety goggles and full faceshield if a splash hazard exists.					
Eye/type.....	Chemical resistant gloves.					
Gloves/ type.....	Wear adequate protective clothes.					
Clothing/type.....	Safety boots per local regulations.					
Footwear/type.....	Eye wash facility and emergency shower should be in close proximity.					
Other/type.....						

PRODUCT: PF 570 WAX BASED PERMANENT RUSTPROOING (AMBER)**SECTION 08: Exposure controls / personal protection**

Appropriate engineering controls..... Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. .

SECTION 09: Physical and chemical properties

Physical state..... Aerosol.
 Colour..... Amber.
 Odour..... Chewing gum.
 Odour threshold (ppm)..... Not available.
 Vapour pressure (mm Hg)..... 65-80 psig @ 21°C .
 Vapour density (air=1)..... >1.
 pH..... No data.
 Relative Density (Specific Gravity)..... 0.660-0.810. (Aerosol). 0.700-0.900. (Liquid).
 Melting / Freezing point (deg C)..... Not Available.
 Solubility..... Insoluble.
 Initial boiling point / boiling range (deg C). No data.
 Evaporation rate..... <1.
 Flash point (deg C), method..... 42°C (108 °F). (estimate for liquid).
 Auto ignition temperature (deg C)..... 460 °C (propellant) .
 Upper flammable limit (% vol)..... 9.5 (For propellant).
 Lower flammable limit (% vol)..... 2.2. (propellant).
 Coefficient of water/oil distribution..... Not available.
 % Volatile by volume..... Not Available.
 VOC..... No data.
 Viscosity..... >20.5 cSt @ 40°C.

SECTION 10: Stability and reactivity

Chemical stability..... Stable at normal temperatures and pressures.
 Reactivity Exposure to high heat.
 Possibility of hazardous reactions..... Hazardous polymerization will not occur.
 Conditions to avoid..... Keep away from heat. Strong oxidizers. Electrostatic charge.
 Hazardous decomposition products..... See hazardous combustion products section 5.

SECTION 11: Toxicological information

INGREDIENTS	LC50	LD50
Solvent naphtha medium aliphatic	>1,400 ppm	3160 mg/kg oral rat
Propane	>1,464 mg/L 15 minutes rat	Not available
Isobutane	52 mg/L 1 hour mouse	Not available
N-Nonane	3200 ppm (4 hrs)	>5000 mg/kg (oral, rat)
Propylene carbonate	Not available	>5000 mg/kg (oral, rat) >2000 mg/kg (dermal, rat)
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Effects of acute exposure.....	Can cause moderate skin irritation. May cause central nervous system effects such as headache, nausea, vomiting and weakness. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.	
Effects of chronic exposure.....	Prolonged or repeated skin contact may cause drying or cracking of skin. Overexposure to vapour may cause central nervous system depression. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .	
Carcinogenicity of material.....	The components of this product are not listed by IARC, NTP or regulated as a carcinogen by OSHA.	
Reproductive effects.....	None.	
Specific Target Organ Toxicity	Causes damage to organs through prolonged or repeated exposure .	

SECTION 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
 Persistence and degradability..... Not available.

PRODUCT: PF 570 WAX BASED PERMANENT RUSTPROOING (AMBER)**SECTION 13: Disposal considerations**

Waste disposal..... Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch. Dispose of as an industrial waste in a manner acceptable to good waste management practice and in accordance with applicable local, provincial/State or federal regulations.

SECTION 14: Transport information

TDG Classification..... UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre.
 DOT Classification (Road)..... UN1950 - AEROSOLS, flammable - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons).
 IATA Classification (Air)..... UN1950 - AEROSOLS, flammable - Class 2.1 - Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
 IMDG Classification (Marine)..... UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity. Check IMDG regulations for limited quantity exemptions.
 Marine Pollutant..... No.
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: Regulatory information

CEPA status..... On Domestic Substances List (DSL).
 TSCA inventory status..... All components are listed.
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous None.
 substances
 Section 311/312 - hazard categories..... Fire hazard. Immediate health, delayed health.
 Section 313..... None.
 EPA hazardous air pollutants (HAPS) None.
 40CFR63
 California Proposition 65..... This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.

SECTION 16: Other information

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Preparation date: APR 06/2018