



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 656C 2.1 VOC 2K URETHANE PRIMER SURFACER - GRAY

SECTION 01: Chemical product and company identification

Manufactured for..... Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario L9T3Y5
Tel (905) 878-4990 Fax (905) 878-1189

Product name..... PF 656C 2.1 VOC 2K URETHANE PRIMER SURFACER - GRAY

Recommended use and restrictions on use Automotive.

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 3 Reactivity: 0.

HMIS..... H: 2 F: 3 R: 0.

24 hour emergency number:..... IN CANADA CALL CANUTEC 1-888-226-8832 (CAN-UTEC); IN THE UNITED STATES
CALL CHEMTREC 1-800-424-9300. .

SECTION 02: Hazards identification



Signal Word..... DANGER.

Hazard Classification..... Flammable Liquid 2. Skin Irritant 2. Eye Irritant 2A. Acute Toxicity (Inhalation) — Category 4. Carcinogenicity — Category 1. Reproductive 2. Specific Target Organ Toxicity — Repeated Exposure — Category 1.

Hazard Description..... H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H350 This product contains ingredients that may cause cancer. H361 This product contains ingredients that are suspected of damaging fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion proof equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe mist, vapours, or spray. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P280 Wear protective gloves and eye protection.

Response P370 + P378 In case of fire - use dry chemical powder, CO2 or foam to extinguish. P303 + P361 + P353 If on skin or in hair: take off all contaminated clothing immediately. Rinse thoroughly with water and use safety shower . P302 + P352 - If on skin: wash with plenty of water. . P362 + P364 - Take off contaminated clothing and wash before reuse. P332 + P313 - If skin irritation occurs get medical attention or advice. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P321 - For specific treatment see section 4 on this SDS.

Storage..... P405 Store locked up. P403 + P235 Store in well ventilated area. Keep cool.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

SECTION 03: Composition/Information on Ingredients

| HAZARDOUS INGREDIENTS | CAS # | WT. % |
|-----------------------|------------|-------|
| Talc | 14807-96-6 | 15-25 |
| tert-Butyl acetate | 540-88-5 | 7-13 |
| N-Butyl Acetate | 123-86-4 | 5-10 |
| Titanium Dioxide | 13463-67-7 | 5-10 |

PRODUCT: PF 656C 2.1 VOC 2K URETHANE PRIMER SURFACER - GRAY**SECTION 03: Composition/Information on Ingredients**

| | | |
|--------------------------|------------|-------|
| 4-Chlorobenzotrifluoride | 98-56-6 | 5-10 |
| Xylene | 1330-20-7 | 3-7 |
| Ethylbenzene | 100-41-4 | 0.1-1 |
| Crystalline Silica | 14808-60-7 | 0.1-1 |

SECTION 04: First aid measures

| | |
|--|---|
| Eye contact..... | In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention. |
| Skin contact..... | Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention. |
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. |
| Ingestion..... | If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, whether acute or delayed | Harmful if swallowed, in contact with skin or if inhaled. Causes skin and eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. This product contains ingredients that are suspected of damaging fertility or the unborn child. This product contains ingredients that may cause cancer. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. |
| Additional information..... | Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

SECTION 05: Fire fighting measures

| | |
|--|---|
| Suitable and unsuitable extinguishing media..... | "Alcohol" foam, CO ₂ , dry chemical. Do not use water in a jet. |
| Hazardous combustion products..... | Oxides of carbon (CO, CO ₂). Hydrocarbons and traces of chlorine compounds. |
| Special fire fighting procedures..... | Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. |

SECTION 06: Accidental release measures

| | |
|-----------------|--|
| Leak/spill..... | Keep away from heat, sparks and flames. Ventilate. Eliminate all sources of ignition. Evacuate all non-essential personnel. Contain the spill. Avoid all personal contact. Prevent runoff into drains, sewers, and other waterways. Absorb with an inert dry material and place in an appropriate waste container. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. |
|-----------------|--|

SECTION 07: Handling and storage

| | |
|--------------------------|---|
| Handling procedures..... | Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking. |
| Storage needs..... | Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight. |

SECTION 08: Exposure controls / personal protection

| INGREDIENTS | TWA | ACGIH TLV | | OSHA PEL | NIOSH |
|--------------------|---------------------|-----------------|-------------------------|---------------------------|------------------------|
| | | STEL | REL | | |
| Talc | 2 mg/m ³ | Not established | 2 mg/m ³ TWA | 3 mg/m ³ - QUE | Not established |
| tert-Butyl acetate | 200 ppm | Not established | 200 ppm | Not established | 200 ppm |
| N-Butyl Acetate | 150 ppm | 200 ppm | 150 ppm | 200 ppm | 150 ppm / STEL 200 ppm |

PRODUCT: PF 656C 2.1 VOC 2K URETHANE PRIMER SURFACER - GRAY**SECTION 08: Exposure controls / personal protection**

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL NIOSH |
|---|---|-------------------|-----------------|------------------|------------------------|
| Titanium Dioxide | 10 mg/m3 | Not established | 15 mg/m3 | Not established | Not established |
| 4-Chlorobenzotrifluoride | Not established | Not established | Not established | Not established | Not established |
| Xylene | 50 ppm | 150 ppm | 100 ppm TWA | Not established | Not established |
| Ethylbenzene | 100 ppm | 125 ppm | 100 ppm | Not established | 100 ppm / STEL 125 ppm |
| Crystalline Silica | 0.025 mg/m3 | Not established | 0.1 mg/m3 TWA | Not established | 0.05 mg/m3 |
| Protective equipment Respiratory/type..... | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. | | | | |
| Eye/type..... | Chemical safety goggles and full faceshield if a splash hazard exists. | | | | |
| Gloves/ type..... | Chemical resistant gloves. | | | | |
| Clothing/type..... | Wear adequate protective clothes. | | | | |
| Footwear/type..... | Safety boots per local regulations. | | | | |
| Other/type..... | Emergency showers and eye wash stations should be available. | | | | |
| Appropriate engineering controls..... | Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. . | | | | |

SECTION 09: Physical and chemical properties

| | |
|--|---|
| Physical state..... | Liquid. |
| Colour..... | Gray. |
| Odour..... | Hydrocarbon odour. |
| Odour threshold (ppm)..... | Not available. |
| Vapour pressure (mm Hg)..... | Not available. |
| Vapour density (air=1)..... | >1. |
| pH..... | Not applicable. |
| Melting / Freezing point (deg C)..... | Not Available. |
| Solubility..... | Slightly soluble in water. |
| Initial boiling point / boiling range (deg C)..... | >95C. |
| Evaporation rate..... | Moderate. |
| Flash point (deg C), method..... | 4.4. (estimate; lowest flash point ingredient). |
| Auto ignition temperature (deg C)..... | > 270. |
| Upper flammable limit (% vol)..... | 10.5. |
| Lower flammable limit (% vol)..... | 0.9. |
| Coefficient of water/oil distribution..... | Not available. |
| Decomposition temperature..... | Not available. |
| % Volatile by volume..... | 55.13. |
| VOC..... | 245.6 g/L - 2.05 lb/USG. |
| Viscosity..... | 3130 cps Spindle #4 @20. |

SECTION 10: Stability and reactivity

| | |
|---|--|
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Reactivity | Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents. |
| Possibility of hazardous reactions..... | Will not occur under normal temperature and pressure. |
| Conditions to avoid..... | Keep away from heat. Incompatible with strong oxidizers. |
| Hazardous decomposition products..... | Oxides of carbon (CO,CO2). Chlorinated hydrocarbons. Thermal decomposition may produce acrid smoke and irritating fumes. |

SECTION 11: Toxicological information

| INGREDIENTS | LC50 | LD50 |
|--------------------|--------------------------|---|
| Talc | Not available | Not available |
| tert-Butyl acetate | >2,230 mg/m3 4 hours rat | 4,100 mg/kg rat oral >2,000 mg/kg rabbit dermal |

PRODUCT: PF 656C 2.1 VOC 2K URETHANE PRIMER SURFACER - GRAY**SECTION 11: Toxicological information**

| INGREDIENTS | LC50 | LD50 |
|--------------------------------------|--|---|
| N-Butyl Acetate | >29.2 mg/L 4 hour rat aerosol 4 hour rat | >3200 mg/kg rat oral >5000 mg/kg rabbit dermal |
| Titanium Dioxide | Not Available | > 10,000 mg/kg rat oral > 10,000 mg/kg rabbit dermal |
| 4-Chlorobenzotrifluoride | 4479 ppm | >6,800 mg/kg rat oral; >2,700 mg/kg rabbit dermal |
| Xylene | 6350 ppm 4 hours rat | >3523 mg/kg rat oral |
| Ethylbenzene | No data | 3,500 mg/kg rat oral 17,800 mg/kg rabbit dermal |
| Crystalline Silica | Not available | >22,500 mg/kg oral rat |
| Route of exposure..... | Eye contact. Skin contact. Inhalation. | |
| Effects of acute exposure..... | Contact with skin may cause moderate to severe irritation. May cause moderate to severe eye irritation. The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation. Inhalation of high vapour may cause central nervous system effects, dizziness, headache, nausea, or loss of coordination. | |
| Effects of chronic exposure..... | Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal . | |
| Carcinogenicity of material..... | This product contains non-asbestiform Talc, which is classified as a Group 3 (not classifiable as to carcinogenicity to humans) by IARC . Ethylbenzene is classified as an A3 known animal carcinogen. IARC has classified Titanium Dioxide as a group 2B carcinogen. Quartz (Crystalline Silica) is listed by IARC in Group 1 as a carcinogen. . | |
| Specific Target Organ Toxicity | Causes damage to organs. | |

SECTION 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
Persistence and degradability..... Not available.

SECTION 13: Disposal considerations

Waste disposal..... Empty containers must be handled with care due to product residue. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

SECTION 14: Transport information

TDG Classification..... UN1263 - PAINT - Class 3 - Packing Group II - This product meets limited quantity exemption when shipped in containers less than 5 litres.
DOT Classification (Road)..... UN1263 - PAINT - Class 3 - Packing Group II - Ltd Qty (1 Liter). Refer to 49CRF 172.101 for additional non-bulk packaging requirements.
IATA Classification (Air)..... UN1263 - PAINT - Class 3 - Packing Group II. Limited Quantity. Do not ship by air without checking appropriate IATA regulations.
IMDG Classification (Marine)..... UN1263 - PAINT- Class 3 - Packing Group II - EmS: F-E S-E. Limited Quantity. Check IMDG regulations for limited quantity exemptions.
Marine Pollutant..... No.
Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: Regulatory information

CEPA status..... On Domestic Substances List (DSL).
TSCA inventory status..... Not determined.
OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III
Section 302 - extremely hazardous None.
Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
Section 313..... Ethylbenzene. Xylene.
EPA hazardous air pollutants (HAPS) Ethylbenzene. Xylene.
40CFR63
California Proposition 65..... *WARNING: This product contains a chemical known to the State of California to cause cancer.

PRODUCT: PF 656C 2.1 VOC 2K URETHANE PRIMER SURFACER - GRAY

SECTION 16: Other information

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Preparation date: JAN 12/2018