



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

GHS classification in accordance with the Hazardous Products Regulations

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Product code : 786097

Details of the supplier of the safety data sheet

Valvoline Canada Corp
905 Winston Churchill Blvd
Mississauga ON L5J 4P2
Canada
1-800-TEAMVAL (1-800-832-6825)

SDS@valvoline.com

Emergency telephone number

1-800-VALVOLINE (1-800-825-8654)

Regulatory Information Number

1-800-TEAMVAL (1-800-832-6825)

Product Information

1-800-TEAMVAL (1-800-832-6825)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**

P280 Wear eye protection/ face protection.

P264 Wash skin thoroughly after handling.

Response:

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	≥ 80.00 - ≤ 100.00
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	≥ 1.00 - < 5.00
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		Not a hazardous substance or mixture.	≥ 1.00 - < 5.00
Zinc O,O',O',O'-tetrakis(1,3- dimethylbutyl) bis(phosphorodithioate	2215-35-2	Skin Irrit. 2; H315 Eye Dam. 1; H318	≥ 1.00 - < 5.00

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
Causes serious eye irritation.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons

Specific extinguishing methods :

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.



SAFETY DATA SHEET
 PREMIUM CONVENTIONAL SAE 10W-30
 Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
- Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		TWA	5 mg/m3 Mist	CA AB OEL
		STEL	10 mg/m3 Mist	CA AB OEL
		TWAEV	5 mg/m3 Mist	CA QC OEL
		STEV	10 mg/m3 Mist	CA QC OEL



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

-
- Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.
- Personal protective equipment**
- Respiratory protection : No personal respiratory protective equipment normally required.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:
Safety shoes
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : 201 - 249 °C
Method: Cleveland open cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Self-ignition : No data available
- Upper explosion limit / Upper flammability limit : No data available



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	0.868 (15.56 °C)
Density	:	0.864 g/cm ³
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	70 mm ² /s (40 °C)
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous reactions	:	Product will not undergo hazardous polymerization.
Conditions to avoid	:	None known.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Acute oral toxicity : LD50 (Rat): 2,230 mg/kg
GLP: no

Acute inhalation toxicity : LC50 (Rat): > 2.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg
Method: OECD Test Guideline 402
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation

Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation

Result : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation

Result : Slight, transient irritation



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate):

Species : Rabbit
Method : OECD Test Guideline 404
Result : Irritating to skin.
GLP : yes

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate):

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate):

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.
GLP : yes

Germ cell mutagenicity

Not classified based on available information.

Components:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate):

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic : Not classified based on available information.
hazard

Long-term (chronic) aquatic : Not classified based on available information.
hazard

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

	Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC (Fish): 10 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Aquatic invertebrates): 10 mg/l
Ecotoxicology Assessment Short-term (acute) aquatic hazard	: Not classified based on available information.
Long-term (chronic) aquatic hazard	: Not classified based on available information.
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate): Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l Exposure time: 96 h Test Type: semi-static test Method: OECD Test Guideline 203 Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 23 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 GLP: yes
Toxicity to algae	: NOEL (Desmodesmus subspicatus (green algae)): 10 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201 Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 0.4 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211 Remarks: Information given is based on data obtained from similar substances.



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

Persistence and degradability

Components:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 1.5 %

Exposure time: 28 d

Method: OECD Test Guideline 301B

Remarks: Information given is based on data obtained from similar substances.

No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n- : log Pow: Expected > 7

octanol/water

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological : No data available
information

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

TDG

Not regulated as a dangerous good

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

Canadian PBT Chemicals : This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA:

Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl)
bis(phosphorodithioate

NPRI Components : Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl)
bis(phosphorodithioate

4259-15-8
100-41-4
108-88-3
71-43-2
91-20-3
123-91-1

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)



SAFETY DATA SHEET
 PREMIUM CONVENTIONAL SAE 10W-30
 Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

SECTION 16. OTHER INFORMATION

Further information

Internal information : R0170829

NFPA:	HMIS III:						
<p align="center">Flammability</p> <p align="center">Special hazard</p>	<table border="1"> <tr> <td>HEALTH</td> <td align="center">2</td> </tr> <tr> <td>FLAMMABILITY</td> <td align="center">1</td> </tr> <tr> <td>PHYSICAL HAZARD</td> <td align="center">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists



SAFETY DATA SHEET
PREMIUM CONVENTIONAL SAE 10W-30
Motor Oil

Version: 1.8

Revision Date: 12/02/2019

Print Date:
12/03/2019

BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System